

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (Previously Presented) A device cooling a CPU chip disposed on a chassis comprising:

a heat sink disposed on the CPU chip;

a bracket, having at least one pivot portion and at least one retention portion, rotatably mounted on the chassis by the pivot portion in one of two positions; and

a fan disposed on the bracket, wherein the fan is relatively closer to the heat sink when the bracket engages with the chassis by the retention portion in a first chassis position, and wherein the fan is relatively farther away from the heat sink when the retention portion of the bracket does not engage the chassis in a second chassis position and the pivot portion still engages the chassis.

Claim 2 (Original) The device as claimed in claim 1, wherein the chassis is provided with at least one pivot recess and at least one retention recess, and the pivot recess is provided with at least one pivot port corresponding to the pivot recess, and the retention portion is provided with at least one retention post corresponding to the retention recess.

Claim 3 (Original) The device as claimed in claim 1, wherein the bracket

is provided with at least one engaging portion, and the fan is provided with at least one second engaging portion corresponding to the first engaging portion.

Claim 4 (Original) The device as claimed in claim 3, wherein the first engaging portion comprises:

- at least one raised pad integrally formed on the bracket; and
- at least one locator post integrally formed on the raised pad.

Claim 5 (Original) The device as claimed in claim 4, wherein the second engaging portion comprises at least one locator recess corresponding to the locator post.

Claim 6 (Original) The device as claimed in claim 1, wherein the bracket is provided with at least one retaining hook for retaining the fan in position.

Claims 7-12 (Cancelled)

Claim 13 (Previously Presented) A fan assembly comprising:  
a bracket having at least one first engaging portion and at least one retaining hook; and

a fan, having a second engaging portion corresponding to the first engaging portion, disposed on the bracket by the retaining hook and the engagement of the first engaging portion and the second engaging portion;

wherein the first engaging portion comprises:

- at least one raised pad integrally formed on the bracket; and
- at least one locator post integrally formed on the raised pad.

Claim 14 (Cancelled)

Claim 15 (Previously Presented) The fan assembly as claimed in claim 13, wherein the second engaging portion comprises at least one locator recess corresponding to the locator post.

Claims 16-21 (Cancelled)